

## **PRODUCT SPECIFICATION**

TRADE NAME: Unisurf SLES 2/30

**CHEMICAL NAME**: Sodium salt of Lauryl Ether Sulphate

## **OTHER PHYSICAL AND CHEMICAL PROPERTIES:**

Sr. No.	Parameters	Specifications	Test Method
1	Appearance	Translucent liquid	Visual method
2	Ethylene oxide moles	2.0	-
3	Mean molecular weight	386	-
4	Colour 5% AM Basis (KLETT)	Max. 30	IS 8401:1994
5	Active matter at M.wt., 386 (% by wt)	28 ± 2.0	IS 11487:1985 A-2
6	Free oil (% by wt)	Max. 2.00	IS 11487:1985 A-3
7	Sodium chloride (% by wt)	Max. 1.0	IS 11487:1985 A-4
8	Sodium sulphate (% by wt)	Max. 1.0	IS 11487:1985 A-5
9	Free Alkalinity as NaOH (% by wt)	Max. 0.5	-
10	Viscosity (cps)	Min. 3000	WI/QA/83

## OTHER INFORMATION:

Packaging	HMHDPE drums of 50 kg and 220 kg nett weight Total of 80 drums i.e. 17.6 MT can be shipped in a 20 ft. full container load		
CAS Number	3088-31-1		
EC Number	221-416-0		

Regd. Off.: Unit No.1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (Sion Trombay Road), Chembur, Mumbai - 71. MH, India, • Fax: +91-22-2524 1895 Tel.: +91-22-2529 9990 / 91 / 92 / 93 / +91-22-4232 4121 • Web: www.unicornpetro.co.in • E-mail: unipetro@vsnl.com, info@unicornpetro.co.in

