

Factory: 10, Vaibhav Industrial Estate, Sion – Trombay Road, Deonar, Mumbai – 400 088, MH, India Phone: +91 – 22 – 2557 6611 / +91 – 22 – 3296 6611 | e-mail: factory@unicornpetro.co.in

PRODUCT SPECIFICATION

PRODUCT: White Petroleum Jelly

GRADE: Ultimo 145/175

TYPICAL PROPERTIES:

CHARACTERS:

Sr. no.	Characteristic	Test Method	Specification
1	Appearance	Visual	A white, translucent, soft unctuous mass, slightly fluorescent in daylight when melted
2	Solubility	BP / USP	Complies
3	Colour (as per USP)	USP	Complies
4	Colour Lovibond, y	IP 17	Not more than 0.5

IDENTIFICATION (as per Ph. Eur.):

Ref. alphabet	Identification	Test Method	Specification
Α	Drop point, °C	BP / Ph. Eur.	45 – 60
С		BP / Ph. Eur.	The solid upper layer is violet pink or brown
D	Appearance	BP / Ph. Eur.	The substance is white. The melted mass is not more intensely coloured than a mixture of 1 volume of yellow primary solution and 9 volumes of 10 g/l solution of hydrochloric acid

IMPURITIES:

Sr. no.	Type of impurity	Test Method	Specification
1	Residue on ignition	USP	Not more than 0.05%
2	Organic acids	USP	Complies
3	Polycyclic aromatic hydrocarbons (PAH)	Ph. Eur.	Complies
4	Fixed Oils, Fats and Rosin	USP	Complies

TESTS:

Sr. no.	Test	Test Method	Specification
1	Alkalinity	USP	Complies
2	Acidity	USP	Complies
3	Consistency at 25°C (0.1 mm)	ASTM D 937	145 – 175
4	Sulphated ash	Ph. Eur.	Not more than 0.05%
5	Kinematic Viscosity at 100 °C, cst	ASTM D 445	3.8 – 5.5
6	Congealing point, °C	ASTM D 938	42 – 52

<u>Remarks</u>: The sample complies with prescribed standards as per Ph. Eur. / USP specifications and USFDA requirements as per 21 CFR 172.880.

This product complies as per ICH Q3C (R4) and USP <467>guidelines for Residual solvents.

PACKING: 190 kg Open mouth drums

